

Diamond Blade

T 56

Type Sintered, Closed Edge

Application High-performance diamond blades for concrete, brick, ceramic, slate and reinforced concrete

Diameter x bore in mm	Max Speed	Max RPM	Segment No	Segment Thickness	Segment Height	Packing	Art.No	Quality
100 x 16	80 m/s	15,300 rpm	CR	2.2	7	1	KW00742	P S
100 x 16	80 m/s	15,300 rpm	CR	2.2	8	1	KW00743	P S
100 x 16	80 m/s	15,300 rpm	CR	2.2	10	1	KW00744	P S
115 x 22	80 m/s	13,300 rpm	CR	2.4	7	1	KW00745	P S
115 x 22	80 m/s	13,300 rpm	CR	2.4	8	1	KW00746	P S
115 x 22	80 m/s	13,300 rpm	CR	2.4	10	1	KW00747	P S
125 x 22	80 m/s	12,250 rpm	CR	2.4	7	1	KW00748	P S
125 x 22	80 m/s	12,250 rpm	CR	2.4	8	1	KW00749	P S
125 x 22	80 m/s	12,250 rpm	CR	2.4	10	1	KW00750	P S
180 x 22	80 m/s	8,500 rpm	CR	2.6	7	1	KW00751	P S
180 x 22	80 m/s	8,500 rpm	CR	2.6	8	1	KW00752	P S
180 x 22	80 m/s	8,500 rpm	CR	2.6	10	1	KW00753	P S
230 x 22	80 m/s	6,650 rpm	CR	3.1	7	1	KW00754	P S
230 x 22	80 m/s	6,650 rpm	CR	3.1	8	1	KW00755	P S
230 x 22	80 m/s	6,650 rpm	CR	3.1	10	1	KW00756	P S
300 x 20	100 m/s	6,400 rpm	CR	3.2	7	1	KW00757	P S
300 x 22	100 m/s	6,400 rpm	CR	3.2	7	1	KW00758	P S
300 x 25.4	100 m/s	6,400 rpm	CR	3.2	7	1	KW00759	P S
300 x 25.4	100 m/s	6,400 rpm	CR	3.2	8	1	KW00760	P S
300 x 25.4	100 m/s	6,400 rpm	CR	3.2	10	1	KW00761	P S
350 x 25.4	100 m/s	5,500 rpm	CR	3.2	7	1	KW00762	P S
350 x 25.4	100 m/s	5,500 rpm	CR	3.2	8	1	KW00763	P S
350 x 30	100 m/s	5,500 rpm	CR	3.2	10	1	KW00764	P S

PROFESSIONAL



STANDARD

