

Grinding Discs

A 30 R-BF

STANDARD

Characteristic High stock removal, long lifetime, efficient, comfortable grinding performance

Field of Application Weld seam preparation, burr removing, levelling, edge grinding, surface grinding



Diameter x Thickness x Bore in mm	Shape	Max Speed	Max RPM	Packing	Art. No
100x4.0x16.0		80 m/s	15,300 rpm	10	KD00174
100x6.0x16.0		80 m/s	15,300 rpm	10	KD00175
100x6.5x16.0		80 m/s	15,300 rpm	10	KD00176
115x4.0x22.2		80 m/s	13,300 rpm	10	KD00177
115x6.0x22.2		80 m/s	13,300 rpm	10	KD00178
115x6.5x22.2		80 m/s	13,300 rpm	10	KD00179
125x4.0x22.2		80 m/s	12,250 rpm	10	KD00180
125x6.0x22.2		80 m/s	12,250 rpm	10	KD00181
125x6.5x22.2		80 m/s	12,250 rpm	10	KD00182
150x4.0x22.2		80 m/s	10,200 rpm	10	KD00183
150x6.0x22.2		80 m/s	10,200 rpm	10	KD00184
150x6.5x22.2		80 m/s	10,200 rpm	10	KD00185
180x4.0x22.2		80 m/s	8,500 rpm	10	KD00186
180x6.0x22.2		80 m/s	8,500 rpm	10	KD00187
180x6.5x22.2		80 m/s	8,500 rpm	10	KD00188
180x8.0x22.2		80 m/s	8,500 rpm	10	KD00189
230x4.0x22.2		80 m/s	6,650 rpm	10	KD00190
230x6.0x22.2		80 m/s	6,650 rpm	10	KD00191
230x6.5x22.2		80 m/s	6,650 rpm	10	KD00192
230x8.0x22.2		80 m/s	6,650 rpm	10	KD00193